

SECTION: _____

 PART: _____



PRODUCT SUBMITTAL DATA

Premium ColorCode™ Banding Tape



DESCRIPTION: Indoor/outdoor grade 4 mil vinyl is excellent for pipe marker banding and pipe color coding.

USE: Use with DuraMark™ Pipe Markers or by itself to indicate content class in piping systems.

COMPLIANCE: ASME (ANSI) A13.1-2020 Scheme for the Identification of Piping Systems for color, color field width & letter size. ANSI Z35.1 Safety Color Codes.
•LEED Compliance: This product is in compliance with Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule#1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). Self-Stick adhesive backing contains less than 3.8g/Liter volatile organic compounds.

Craftmark's Premium Color-Code Tape is made of premium/ultra durable vinyl and is available in 10 colors and 4 widths! Rolls meet ASME color field recommendations when used with DuraMark™ pipe markers. Tape is liner mounted-just cut, remove liner and wrap around the pipe.

FEATURES

- 4 Stock Widths 1", 2", 4", 6"
- Full 50' Rolls.
- Premium 4 mil vinyl
- 5-7 year outdoor life
- Aggressive liner mounted adhesive backing.

•STANDARD COLORS



RED



BLUE



GREEN



YELLOW



ORANGE



VIOLET



BLACK



BROWN



WHITE



CLEAR

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____

Premium ColorCode™ Banding Tape (Continued)

ADHESIVE: Permanent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

CHEMICAL RESISTANCE:

MOISTURE RESISTANCE: EXCELLENT moisture resistance

ABRASION RESISTANCE: VERY GOOD abrasion resistance

GLOSS: 60 Gardner units (20° test)

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____