

SECTION:

PART:


CRAFTMARK
PIPE MARKERS ▲ SINCE 1959

GLOBAL MECHANICAL IDENTIFICATION SOLUTIONS™



PRODUCT SUBMITTAL DATA

SpecMark™ FP Fire Protection Snap On™ Pipe Marker



SpecMark™ FP Precoiled & Pretensioned Plastic Markers save installation time and labor costs!

Craftmark's SpecMark™ FP conform 100% to ASME (ANSI) A13.1-2020 Standard "Scheme for the Identification of Piping Systems". We use only the most durable materials and UV screen inks. These durable markers are used on wet, oily, cold, dirty, or rusty pipes, where pressure sensitives won't stick! No preparation of the pipe surface is required before application so valuable labor time is saved!

FEATURES

- Meets ASME (ANSI) A13.1-2020 Standard-100%
- No pipe preparation necessary.
- 360° visibility-Styles AA-F
- Installs quickly in new and existing facilities.
- Can be removed and re-used.
- Markers come with preprinted arrows.
- Choose from over 300 stock legends.
- Available in 7 standard coiled sizes.
- Sizes G-H supplied with Black Nylon, UV stabilized ties.
- Sizes to fit 3/8" thru 40"
- Coiled plastic is lightweight yet durable.
- Coiled marker snaps around pipe with ease.
- Heavy 20 mil vinyl on sizes AA-B.
- Super Heavy-duty 30mil vinyl on sizes C,D,E,F,G,H
- Custom available with no set-up charges or hidden minimum orders. Order 1 with no set-up charge!

DESCRIPTION: SpecMark™ FP (sizes AA-F) are precoiled & pretensioned printed sheet that are designed to snap around the pipe and stay there without need for adhesive. Sizes G-H are supplied flat and are installed with factory supplied UV stable black nylon ties.

USE: For marking all varieties of pipe-especially rusty, wet, damp, oily or especially dirty pipe. Also used as a labor saver on installations. Use indoor or outdoor.

COMPLIANCE: Complies 100% to ASME (ANSI) A13.1-2020 Scheme for the Identification of Piping Systems for color, color field width & letter size. Complies with ANSI Z535.1 Safety Color Code

•LEED Compliance: This product is in compliance with Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule#1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC).

•UL94-Test for Flammability of plastic materials 94V-0

•SpecMark™ FP Snap On® Application Guide

STYLE A

- For pipe diameters 3/4" - 1"
8" marker width, 1/2" letters



STYLE B

- For pipe diameters 1 1/8" - 2 3/8"
8" marker width, 3/4" letters



STYLE C

- For pipe diameters 2 1/2" - 3 1/4"
12" marker width, 1 1/4" letters



STYLE D

- For pipe diameters 3 3/8" - 4 1/2"
12" marker width, 1 1/4" letters



STYLE E

- For pipe diameters 4 5/8" - 5 7/8"
12" marker width, 1 1/4" letters



STYLE F

- For pipe diameters 6" - 8"
12" marker width, 1 1/4" letters



STYLE G

- For pipe diameters 8" - 10"
24" marker width, 2 1/2" letters



NOT 360° Visibility

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____

SpecMark™ FP Fire Protection Snap On™ Pipe Marker (Continued)

ADHESIVE: N/A - No need for adhesive

SURFACE PREPARATION: NONE NEEDED - A huge labor saver.

SERVICE TEMPERATURE: Sizes A-H -40°F to 180°F (-40°C to 82°C)

APPLICATION TEMPERATURE: N/A

AVERAGE OUTDOOR DURABILITY: 5-8 years average. Results vary based on locations, environmental conditions & varies with background color.

CHEMICAL RESISTANCE: Excellent resistance to most petroleum solvents and low aliphatic alcohols.

MOISTURE RESISTANCE: EXCELLENT

ABRASION RESISTANCE: EXCELLENT

GLOSS: 60 units (20° test)

STORAGE STABILITY: Indefinite storage & shelf life when stored at 70°F (21°C) and relative humidity.

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____