DIAMOND PROTECH® NANODIAMOND COATING TECHNOLOGY

NANODIAMOND COATING



DIAMOND BODY Super-Hydrophobic 18 Mo

Super-Hydrophobic 18 Month Coating

Diamond Body is our breakthrough nanodiamond coating that doesn't require professional training to achieve amazing, hydrophobic results on your vehicle. Prep the car then apply with ease. Diamond Body will yield up to 18 months of hydrophobic protection.

APPLICATION INSTRUCTIONS

PRECAUTIONS

Apply in temperatures between 10-30C, 50-90F.

Apply in a closed, well ventilated, indoor area with air humidity not exceeding 70%.

Use fresh suede & microfiber towels for application of additional layers (do not use previously used towels).

APPLICATION TIPS

Hand polish/buff after application (do not use machine tool). Apply to headlights, rubber and metal trim elements. If application in hot climate (over 30 C/90F), lower flashing time, polish the treated surfaces immediately. Use an additional light source to control your work when polishing treated surfaces.

WHAT YOU'LL NEED

- 2 Microfiber Towels
- Applicator
- Diamond Body Prep
- Protective Gloves

BEFORE APPLYING - CLEANING AND DECONTAMINATION

Be sure to apply Diamond Body Prep or an Isopropyl Alcohol degreaser to ensure there are no remnants of polishes or wax.

Wipe down with a damp microfiber towel to remove any residues left from the cleaning product used. Allow the surface to dry completely before application of Diamond Body.

APPLICATION - ESTIMATED APPLICATION TIME: 30 min | 1 LAYER



Shake well for 15 seconds. Apply 8-10 drops on a microfiber applicator.



Apply to 1 element of the car in crosshatch fashion. Wait 1 minute to allow the product to bond to the surface.



Begin to polish the treated surfaces with a clean microfiber towel to level and evenly spread the coating. Use an additional light source to control your work, taking care to remove any excess residue in the process.



Immediately after application of Diamond Body the car is ready for exploitation.