











Smart anti-fatigue mat with a distinctive bubbled surface









- · High-quality anti-fatigue mat.
- Raised bubble patterned surface encourages movement and stimulates circulation, reliably preventing signs of fatigue.
- · Increased work safety due to slip resistance.
- NBR rubber (nitrile) for good resistance to oil, lubricants and chemicals
- Available as individual mats or interlocking sections for longer production lines



Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk

Parts

Part Number	Size	Colour	Weight (kg)
BF010001N	0.6 m x 0.9 m	Black (Nitrile)	5
BF010002N	0.9 m x 1.2 m	Black (Nitrile)	11
BF010003N	0.6 m x 0.9 m	Black (Nitrile)	5
BF010004N	0.6 m x 0.9 m	Black (Nitrile)	5

Technical Specifications

Material	NBR	
Recycled Material Content %	22.3%	
Surface Finish	Bubble	
Product Height	14 mm	
Min. Operating Temperature	-20°C	
Max. Operating Temperature	+50°C	
Resistance to Chemicals	NBR offers excellent resistance to oils and chemicals	
Environmental Resistance	Suitable for predominantly dry environments	
UV Resistance	Yes	
Typical Applications	General industrial	
Installation Method	Loose lay interlocking mats	
Cleaning Method	Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats	
COO (Country of Origin)	LK	
Tensile Strength	3 MPa	
Elongation	250%	
Application Temperature	-30°C to 50°C	
Manufacturing process	Compression moulding	



Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk