



## **Bubblemat Safety**

Smart anti-fatigue mat with a distinctive bubbled surface









- · Highly effective anti-fatigue mat.
- Edges in yellow signal colour for increased work safety.
- The bubbles of this workplace mat encourage more movement and stimulate the circulation, reliably preventing signs of fatigue.
- · Increases safety at the workplace as an anti-slip mat.
- Ideal for standing workplaces in industry and manufacturing.
- · Available as individual mats or interlocking modules.



Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk

## **Parts**

Part Number	Size	Colour	Weight (kg)
BF010701	0.6 m x 0.9 m	Safety	5
BF010702	0.9 m x 1.2 m	Safety	11
BF010703	0.6 m x 0.9 m	Safety	5
BF010704	0.6 m x 0.9 m	Safety	11
BF010705	0.9 m x 1.2 m	Safety	11
BF010706	0.9 m x 1.2 m	Safety	11

## **Technical Specifications**

Material	Natural rubber
Surface Finish	Bubble
Product Height	14 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+50°C
Resistance to Chemicals	Not resistant to fat and mineral oil
Environmental Resistance	Suitable for predominantly dry environments
UV Resistance	Yes
Typical Applications	General industrial
Installation Method	Loose lay interlocking mats
Cleaning Method	Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats
COO (Country of Origin)	LK
Tensile Strength	3 MPa
Elongation	250%
Application Temperature	-30°C to 50°C
Manufacturing process	Compression moulding
Applications Installation Method  Cleaning Method  COO (Country of Origin)  Tensile Strength  Elongation  Application Temperature  Manufacturing	Loose lay interlocking mats  Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats  LK  3 MPa  250%  -30°C to 50°C



**Tel:** 01724 281044 **Web:** www.fireandsafetycentre.co.uk **Email:** sales@fireandsafetycentre.co.uk