



Deckplate Anti-Static

Hardwearing dual layer mat for static sensitive areas



- Hardwearing anti-fatigue mat for static sensitive areas.
- Conductive top surface protects operatives and components.
- Diamond pattern surface is attractive and slip resistant.
- Top surface provides resilience to many industrial chemicals.
- Grounded via a 10 mm male stud fitted to the mat.
- Supplied with ramped edges as standard to reduce the risk of trips.
- Tested to EN14041 resistance requirements.
- Rv: $9.8 \times 10^7 \Omega$



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk

Parts

Part Number	Size	Colour	Weight (kg)
DPS010005	0.9 m x 18.3 m	Black	108
DPS010005C	0.9 m x per linear metre	Black	8
DPS010007	1.2 m x 18.3 m	Black	166
DPS010007C	1.2 m x per linear metre	Black	9
DPS010609	0.6 m x 0.9 m	Black	3.54
DPS010915	0.9 m x 1.5 m	Black	8.86

Technical Specifications

Material	Vinyl top surface with PVC foam backing (fusion bonded, not glued)
Surface Finish	Diamond pattern
Product Height	14 mm
Min. Operating Temperature	0°C
Max. Operating Temperature	+60°C
Resistance to Chemicals	The PVC top surface provides limited resistance to chemicals and oils
Environmental Resistance	Suitable for dry indoor environments
COO (Country of Origin)	CN
Guarantee	3 years when used in dry environment

Additional Information



Deckplate AS - ESD Test BS EN 14041



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre
15 Atkinsons Way, Foxhills Industrial Estate
Scunthorpe, North Lincolnshire, DN15 8QJ
Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk
Email: sales@fireandsafetycentre.co.uk