



Helping to protect lives globally

JoBird®

BUILT BY THE BEST TO WITHSTAND THE WORST.

Product data sheet

JB83BA 1 x SCBA Cabinet



Typical use:

For the storage of 1 x 30-60 minute Self contained breathing apparatus. Designed to cope with extreme environments on and offshore. It is widely used by the world's top energy company due to its durability.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for the fire extinguisher in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a nylon rotary handle with anti-tamper facility to guarantee fast access in an emergency even when wearing gloves.

The SCBA is held in place by a plastic coated sprung clip.

Standard specification:

Dimensions (mm)

Height x width x depth: 816 x 548 x 344

Aperture: 662H x 395W

Internal depth: 275

Weight Kg: 11.5Kg

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinge: 316 Stainless steel

Handle: Nylon/316 Stainless steel rotary with Biomaster® anti-microbial additive and anti-tamper seal facility

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window

Heater for cold climates



Made in the UK



Fire and Safety Centre

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk



Helping to protect lives globally

JoBird®

BUILT BY THE BEST TO
WITHSTAND THE WORST.

Product data sheet

JB54BA Breathing Apparatus Cabinet



Typical use:

For the storage of a double full duration set. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

This cabinet comes fitted with 2 x BA clips.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 857 x 1070 x 435

Aperture: 692H x 868W

Weight Kg: 19Kg

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: Stainless Steel

Handle: Recessed nylon rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel



Manufactured in the UK



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB08BA 4 x SCBA cabinet



Typical use:

For the storage of 4 x Self contained 30-60 minute breathing apparatus. This cabinet is widely used in the Offshore energy sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The cabinet comes fitted with 1 central shelf and four plastic coated sprung clips to hold the SCBAs in place.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 1475 x 916 x 460

Aperture: 1234H x 699W

Internal depth: 388

Weight Kg: 35Kg

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

316 Stainless steel 3 way locking

Double doors



Manufactured in the UK



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate
Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk