

Jo Bird®

BUILT BY **THE BEST** TO WITHSTAND THE WORST.

Product data sheet



JB10FE Firefighter's Equipment Cabinet

Typical use:

For the storage of 1 complete set of firefighter's equipment, including SCBA. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with gelcoat 316 stainless steel nuts, bolts and washers.

The cabinet comes fitted with 1 shelf and 1 BA clip to hold the SCBA. The uniform is stored folded on the shelf.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 1304 x 788 x 469

Aperture: 1052H x 570W

Internal depth: 415

Weight Kg: 22Kg

Material specification:

Colour: Red RAL3000

Material: Lloyds approved composites with UV stabilised

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours

316 Stainless steel 3 way locking

Class 1 fire retardant composites

Perspex window with bezel

Manufactured in the UK















Available From:

Fire and Safety Centre 15 Atkinsons Way, Foxhills Industrial Estate Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk



Bird®

BUILT BY **THE BEST** TO WITHSTAND THE WORST.

Product data sheet

JB08FE Fire Fighter's Equipment cabinet



Typical use:

For the storage of 2 sets of Fire fighter's equipment including SCBA with uniforms folded on a shelf. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The cabinet comes fitted with 1 shelf and 2 plastic coated sprung clips to hold the SCBAs in place.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 1475 x 916 x 460

Aperture: 1234H x 699W

Internal depth: 388

Weight Kg: 35Kg

Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised

gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

316 Stainless steel 3 way locking

Double doors

Heating and insulation















Manufactured in the UK



Available From:

Fire and Safety Centre 15 Atkinsons Way, Foxhills Industrial Estate Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk

Bird®

BUILT BY **THE BEST** TO WITHSTAND **THE WORST.**

Product data sheet

JB17FE Fireman's Equipment Cabinet



Typical use:

For storage of 2 x firefighters clothing hanging c/w CABA. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

This cabinet is fitted with 2 x BA clips, shelves and a hang rail.

The interlocking doors are opened using a Stainless steel L handle to guarantee fast access even when wearing gloves.











Standard specification:

Dimensions (mm)

Height x width x depth: 2015 x 1385 x 460

Aperture: 1739H x 1164W

Internal depth: 405

Weight Kg: 50Kg

Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV

stabilised gelcoat

Hinges: 316 Stainless steel

Handle: 316 Stainless steel L handle

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Heating and insulation

316 stainless steel door stays

Vents

Manufactured in the UK





Available From:

Fire and Safety Centre 15 Atkinsons Way, Foxhills Industrial Estate Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk