



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO  
WITHSTAND **THE WORST.**

## Product **data sheet**

# 10-20m Fire Hose Cabinet (JB80)



### Typical use:

For the storage of 1 x 10- 20m firehose and nozzle. This cabinet is widely used in the Offshore energy and marine sectors.

### Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a rotary graphite nylon handle with anti-microbial additive which can be fitted with an anti-tamper seal. The large yellow handle is easy to rotate to open the door and guarantee fast access even when wearing gloves.

### Standard specification:

Dimensions (mm)

Height x width x depth: 524 x 561 x 198

Aperture: 374H x 414W

Internal depth: 162

Weight Kg: 6.1Kg

### Material specification:

Colour: Red RAL3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Graphite Rotary/316 Stainless steel with anti-microbial additive.

Seal: EPDM

### Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window



Manufactured in the UK



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate  
Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO  
WITHSTAND **THE WORST.**

## Product **data sheet**

# JB85 Hydrant Equipment Cabinet

### Typical use:

For the storage of 1 x of 20m firehose and nozzle. This cabinet is widely used in the Offshore energy and marine sectors.

### Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are manufactured in 316 stainless steel.

The door can be specified with left or right hinging and features a rotary graphite nylon handle to enable fast access even when wearing gloves. An anti-tamper seal can be added.

### Standard specification:

Dimensions (mm)

Height x width x depth: 613 x 670 x 185

Aperture: 460H x 520W

Internal depth: 144

Weight Kg: 9Kg

### Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges and hose pin: 316 Stainless steel

Handle: Rotary graphite nylon with anti-tamper seal & Biomaster® anti-microbial additive

Seal: EPDM

### Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window

Ground mounting posts

Manufactured in the UK



This model replaces the JB16 and JB16R cabinets



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate  
Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)





Helping to protect lives globally

JoBird®

BUILT BY THE BEST TO  
WITHSTAND THE WORST.

## Product data sheet

# JB85.360H Hydrant Equipment Cabinet



This model replaces the JB16.360H and JB16.360HR

### Typical use:

For the storage of 2 x lengths of 20m firehose and nozzles. This cabinet is widely used in the Offshore energy and marine sectors.

### Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are manufactured in 316 stainless steel.

The fire hoses are held securely on a 316 Stainless steel hose pin.

The door can be specified with left or right hinging and features a rotary graphite nylon handle to enable fast access even when wearing gloves. An anti-tamper seal can be added.

### Standard specification:

Dimensions (mm)

Height x width x depth: 626 x 680 x 331

Aperture: 460H x 520W

Internal depth: 290

Weight Kg: 10Kg

### Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges and hose pin: 316 Stainless steel

Handle: Rotary graphite nylon with anti-tamper seal & Biomaster® anti-microbial additive

Seal: EPDM

### Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window

Ground mounting posts

Manufactured in the UK



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate  
Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)



Helping to protect lives globally

Jo**Bird**<sup>®</sup>

BUILT BY **THE BEST** TO  
WITHSTAND **THE WORST.**

## Product **data sheet**

# 2 x 30M Fire Hose cabinet (JB02HR)



### Typical use:

For the storage of 2 x 30M Fire hoses and branch pipe. For on and offshore use. It is widely used by the world's top energy company due to its durability.

### Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for the fire Hoses in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a Graphite nylon rotary door handle to guarantee fast access in an emergency even when wearing gloves. It can also be fitted with an anti-tamper seal.

Fitted with a 316 stainless steel hose pin to neatly store the fire hoses.

### Standard specification:

Dimensions: 937 x 835 x 347 mm (H x W x D)

36.89 x 32.87 x 13.67 inches

Aperture: 756H x 628W (mm) 29.76 x 24.72"

Internal depth: 293 (mm) 11.54"

Weight Kg: 15Kg (33Lb)

### Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon /316 Stainless steel with Biomaster<sup>®</sup> anti-microbial technology and anti-tamper seal facility

Seal: EPDM

### Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window

Nylon straps with quick release buckles

Heater and insulation

Made in the UK



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)





Helping to protect lives globally

**JoBird®**

**BUILT BY THE BEST TO  
WITHSTAND THE WORST.**

## Product data sheet

# JB14H 4 x 23m Fire Hose Cabinet



### Typical use:

For the storage of 4 x 23m fire hoses and 2 x water nozzles. This cabinet is widely used in the Offshore energy and marine sectors.

### Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The cabinet comes fitted with 2 x 316SS hose pins to hold the hoses.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

### Standard specification:

Dimensions (mm)

Height x width x depth: 1296 x 698 x 392

Aperture: 1060H x 490W

Internal depth: 320

Weight Kg: 24Kg

### Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

### Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

316 Stainless steel 3 way locking



Manufactured in the UK



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO  
WITHSTAND **THE WORST.**

## Product data sheet

# JB10H Fire Hose Cabinet



### Typical use:

For the storage of 4 x 30M fire hoses and 2 x water nozzles. This cabinet is widely used in the Offshore energy and marine sectors.

### Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The cabinet comes fitted with 2 x 316SS hose pins to hold the hoses, 1 x 316SS double nozzle bracket for the water nozzles.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

### Standard specification:

Dimensions (mm)

Height x width x depth: 1302 x 788 x 469

Aperture: 1062H x 570W

Internal depth: 415

Weight Kg: 22Kg

### Material specification:

Colour: Red RAL3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

### Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

316 Stainless steel 3 way locking

Double doors



Manufactured in the UK



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)