



Helping to protect lives globally

Jo**Bird**[®]

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB87HS Swinging hose reel cabinet



Typical use:

For the storage of 1 x Swinging Fire hose reel (not included). For on and offshore use. It is widely used by the world's top energy company due to its durability.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for the fire Hoses in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a nylon rotary handle with Biomaster[®] technology anti-tamper seal facility for rapid access in an emergency even when wearing gloves.

The sides or back can be reinforced depending on how the hose reel assembly is fitted.

Standard specification:

Dimensions (mm)

Height x width x depth: 920 x 835 x 316

Aperture: 755H x 676W

Internal depth: 275

Weight Kg: 15Kg

Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon/316 Stainless steel Biomaster[®] technology

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window

Heating and insulation

Manufactured in the UK

This model replaces the JB02HS



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk



Helping to protect lives globally

Jo**Bird**[®]

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB54HOSEREEL Fire Hose Reel Cabinet



Typical use:

For the storage of a Swinging Hose reel (not supplied). This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves. The reel can be fitted to either side which is reinforced to take the weight of the reel and bracket.

Standard specification:

Dimensions (mm)

Height x width x depth: 857 x 1070 x 435

Aperture: 692H x 868W

Weight Kg: 19Kg

Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Recessed nylon rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

Heater and insulation

Vents

316 Stainless steel 3 way locking

Manufactured in the UK



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB64 Horizontal Fire Hose Cabinet



Typical use:

For the storage of a horizontal Fire Hose reel. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a recessed nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 1000 x 1050 x 850

Aperture: 793H x 833W

Internal depth: 796

Weight Kg: 28 Kg

Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless Steel

Handle: Recessed nylon rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

3 way locking with stainless steel L handle

Double doors

Manufactured in the UK



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk