



## Orthomat® Dot


Simple but effective workplace mat




- Single layer foam anti-fatigue mat.
- Dot pattern surface for more grip, reduces slip risk.
- Insulates standing workers against the effects of cold concrete floors.
- Lightweight, so easy to transport and reposition.
- Best suited to dry environments.
- High visibility version available with bright yellow borders.
- Ideal for lighter industrial use.
- Available in mats and rolls.
- Fire tested to BS EN 13501-1.



### Styles Available



Standard



Safety



**Fire and Safety  
Centre**

**Available From:**

Fire and Safety Centre  
15 Atkinsons Way, Foxhills Industrial Estate  
Scunthorpe, North Lincolnshire, DN15 8QJ  
**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)  
**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)

## Parts

Part Number	Size	Colour	Weight (kg)
AD010001	0.6 m x 0.9 m	Black	1.31
AD010002	0.9 m x 1.5 m	Black	3.27
AD010003	0.9 m x 18.3 m	Black	50
AD010003C	0.9 m x per linear metre	Black	2.7
AD010005	1.2 m x 18.3 m	Black	50
AD010005C	1.2 m x per linear metre	Black	3.03
AD010701	0.6 m x 0.9 m	Black/Yellow	1.31
AD010702	0.9 m x 1.5 m	Black/Yellow	3.27
AD010703	0.9 m x 18.3 m	Black/Yellow	50
AD010703C	0.9 m x per linear metre	Black/Yellow	2.7
AD010705	1.2 m x 18.3 m	Black/Yellow	66
AD010705C	1.2 m x per linear metre	Black/Yellow	3.6

## Technical Specifications

<b>Material</b>	Open Cell PVC (Foam)
<b>Surface Finish</b>	Dot pattern
<b>Product Height</b>	9.5 mm
<b>Size of Safety Border</b>	100 mm
<b>Min. Operating Temperature</b>	0°C
<b>Max. Operating Temperature</b>	+60°C
<b>Environmental Resistance</b>	Suitable for dry indoor environments only
<b>Typical Applications</b>	Production lines, Assembly areas, Packing stations, Workbenches
<b>Installation Method</b>	Loose lay
<b>Cleaning Method</b>	Brush/mop the top surface
<b>COO (Country of Origin)</b>	CN
<b>Guarantee</b>	1 year when used in a dry environment
<b>Adhesive recommended by F.Ball for permanent bond</b>	F44
<b>Tackifier recommended by F.Ball</b>	F41
<b>Adhesive recommended by F.Ball for heavy-duty/wet areas</b>	F74, F81, F84

## Additional Information



Orthomat Fire Test EN ISO 11925



Orthomat Fire Test BS EN 13501



Orthomat Fire Test EN ISO 9239



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate  
Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)