



## Orthomat® Standard

Quickly tackle standing fatigue in dry workplaces



- Versatile single layer foam anti-fatigue mat.
- Insulates standing workers against the effects of cold concrete floors.
- Lightweight, so easy to transport and reposition.
- Best suited to dry environments.
- High visibility version available with bright yellow borders.
- Ideal for lighter industrial use.
- Textured surface provides attractive appearance.
- Available in mats and rolls.
- Fire tested to BS EN 13501-1.



**Fire and Safety  
Centre**

**Available From:**

Fire and Safety Centre  
15 Atkinsons Way, Foxhills Industrial Estate  
Scunthorpe, North Lincolnshire, DN15 8QJ  
**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)  
**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)

## Styles Available



Black



Grey



Safety

## Parts

Part Number	Size	Colour	Weight (kg)
AF010001	0.6 m x 0.9 m	Black	1.31
AF010002	0.9 m x 1.5 m	Black	3.27
AF010003	0.9 m x 18.3 m	Black	40
AF010003C	0.9 m x per linear metre	Black	1.6
AF010004	0.45 m x 0.9 m	Black	
AF010005	1.2 m x 18.3 m	Black	58.55
AF010005C	1.2 m x per linear metre	Black	2.1
AF010701	0.6 m x 0.9 m	Black/Yellow	1.31
AF010702	0.9 m x 1.5 m	Black/Yellow	3.27
AF010703	0.9 m x 18.3 m	Black/Yellow	40
AF010703C	0.9 m x per linear metre	Black/Yellow	3.01
AF010706	1.2 m x 18.3 m	Black/Yellow	70
AF010706C	1.2 m x per linear metre	Black/Yellow	2.1
AF060001	0.6 m x 0.9 m	Grey	1.31
AF060002	0.9 m x 1.5 m	Grey	3.27
AF060003	0.9 m x 18.3 m	Grey	40
AF060003C	0.9 m x per linear metre	Grey	2

## Technical Specifications

<b>Material</b>	Open Cell PVC (Foam)
<b>Surface Finish</b>	Pebble
<b>Product Height</b>	9.5 mm
<b>Roll Length</b>	18.3 m
<b>Size of Safety Border</b>	100 mm
<b>Min. Operating Temperature</b>	0°C
<b>Max. Operating Temperature</b>	+60°C
<b>Environmental Resistance</b>	Suitable for dry indoor environments
<b>Typical Applications</b>	Production lines, Assembly areas, Packing stations, Workbenches
<b>Installation Method</b>	Loose lay
<b>Cleaning Method</b>	Brush/mop the top surface
<b>Fire Tested to</b>	BS EN 13501-1 Class Dfl - s1
<b>COO (Country of Origin)</b>	CN
<b>Guarantee</b>	1 year when used in a dry environment
<b>Adhesive recommended by F.Ball for permanent bond</b>	F44
<b>Tackifier recommended by F.Ball</b>	F41
<b>Adhesive recommended by F.Ball for heavy-duty/wet areas</b>	F74, F81, F84

## Additional Information



Orthomat Fire Test BS EN 13501



Orthomat Fire Test EN ISO 11925



Orthomat Fire Test EN ISO 9239



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate  
Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)