



## Rampmat

A popular honeycomb mat for all environments



- A popular choice of doormat, suitable for most climates.
- The raised honeycomb design provides grip while scraping away dirt and moisture.
- Moulded bevelled edging for trip-resistance and wheeled access.
- Manufactured from durable rubber.
- Slip tested to DIN 51130.



**Fire and Safety  
Centre**

**Available From:**

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)

## Parts

| Part Number | Size          | Colour | Weight (kg) |
|-------------|---------------|--------|-------------|
| RP010001    | 0.9 m x 1.5 m | Black  | 8           |
| RP010002    | 0.8 m x 1.2 m | Black  | 5           |

## Technical Specifications

|                                    |   |
|------------------------------------|---|
| <b>Material</b>                    | Rubber mix, including >50% recycled material  |
| <b>Recycled Material Content %</b> | 70  |
| <b>Surface Finish</b>              | Raised circular surface   |
| <b>Product Height</b>              | 14 mm   |
| <b>Min. Operating Temperature</b>  | -20°C   |
| <b>Max. Operating Temperature</b>  | +130°C  |
| <b>Environmental Resistance</b>    | Suitable for wet and dry environments, indoors or outdoors  |
| <b>Typical Applications</b>        | General industrial, Areas where swarf is prevalent. Entrance areas.                                   |
| <b>Installation Method</b>         | Loose lay   |
| <b>Cleaning Method</b>             | Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt                          |
| <b>COO (Country of Origin)</b>     | IN  |
| <b>Tensile Strength</b>            | 2.75 to 3.25 MPa  |
| <b>Notes</b>                       | Silicone is used in the production process of the mats and a residue will possibly be left on the mat |
| <b>Slip Tested to</b>              | DIN 51130 - R10   |

## Additional Information



Rampmat Ramp Slip Test DIN 51130



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre  
15 Atkinsons Way, Foxhills Industrial Estate  
Scunthorpe, North Lincolnshire, DN15 8QJ  
**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)  
**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)