



Helping to protect lives globally

Jo**Bird**<sup>®</sup>

BUILT BY THE BEST TO  
WITHSTAND THE WORST.

## Product data sheet

# RS100H Hydrant Equipment Cabinet



### Typical use:

For the storage of 4 x 20M lengths firehose and branch pipes. This cabinet is widely used in the Offshore energy and marine sectors.

### Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The roller shutter door enables access in confined spaces. The AS shutters used have proved to be extremely durable over a very long period of time.

It comes with 2 x 316 Stainless steel hose pins to hold the fire hoses in place.

### Standard specification:

Dimensions (mm)

Height x width x depth: 1085 x 925 x 353

Aperture: 675H x 730W

Internal depth: 300

Weight Kg: 30.5 Kg

### Material specification:

Colour: Red RAL3000

Material: Lloyds approved composites with UV stabilised gelcoat

Lettering: "Fire Hose" 50mm white

Roller Shutter: Extreme environment Roller Shutter in Aluminium

### Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Vents

Shelves instead of hose pins



Manufactured in the UK



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

Email: [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO  
WITHSTAND **THE WORST.**

## Product data sheet

# RS150H 4 x 30m Fire hose Cabinet



### Typical use:

For the storage of 4 x 30m fire hoses. This cabinet is widely used in the Offshore energy and marine sectors.

### Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The roller shutter door enables access in confined spaces. The AS shutters used have proved to be extremely durable over a very long period of time.

This cabinet comes fitted with 2 x Stainless hose pins and 1 x double nozzle bracket.

### Standard specification:

Dimensions (mm)

Height x width x depth: 1550 X 776 X 491

Aperture: 1085H x 608W

Internal depth: 404

Weight Kg: 60 Kg

### Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Lettering: "FIRE HOSE" 50mm white

Roller Shutter: Extreme environment Roller Shutter in Aluminium

### Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Heating and insulation

Manufactured in the UK



**Fire and Safety  
Centre**

### Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

**Tel:** 01724 281044 **Web:** [www.fireandsafetycentre.co.uk](http://www.fireandsafetycentre.co.uk)

**Email:** [sales@fireandsafetycentre.co.uk](mailto:sales@fireandsafetycentre.co.uk)