

Safe and approved storage of flammable hazardous substances in working areas

Function / construction:

- Robust construction and longevity: body made of powdercoated sheet steel
- User-friendly: drawer remains open in any position, interior of drawer completely visible – access to all containers
- Safe: drawer fitted with earthing wire incl. clamp as standard, seal welded sump, drawers are self-closing in the event of fire
- No unauthorised use: drawer lockable with cylinder lock and locking state indicator (red/green)
- Mobile: castors with plinth (optionally available), easy moving of the cabinet
- **Ventilation:** integrated air ducts ready for connection (DN 50) to a technical exhaust system



Dimensions	
Width (external)	593.00 mm
Depth (external)	600.00 mm
Height (external)	800.00 mm
Width (internal)	470.00 mm
Depth (internal)	482.00 mm
Height (internal)	702.00 mm
The available internal dimensions can vary depend	fing on the interior equipment package

Weight / Load	
Weight without interior equipment	143 kg
Distributed load	467.00 kg/m ²
Maximum load	300 kg

Ventilation		
Extraction air	50 DN	
minimum exhaust air quantity 10 times	2 m³/h	
Pressure drop inside the cabinet	1 Pa	

Colouring / Surface finish	
Body colour code	RAL 7035
Body colour	Light grey
Body surface finish	plain
Door / Drawer colour code	RAL 7035
Door / Drawer colour	Light grey
Door / Drawer surface finish	plain

General Information	
Number of drawers	1
Capacity drawer	21.5 litres
Customs tariff number	94032080



Available From:

Fire and Safety Centre 15 Atkinsons Way, Foxhills Industrial Estate Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk




















Safe and approved storage of flammable hazardous substances in working areas

Function / construction:

- Robust construction and longevity: body made of powdercoated sheet steel
- User-friendly: drawers remain open in any position, interior of drawers completely visible – access to all containers
- Safe: drawers fitted with earthing wire incl. clamp as standard, seal welded sump, drawers are self-closing in the event of fire
- No unauthorised use: drawers lockable with cylinder lock and locking state indicator (red/green)
- Mobile: castors with plinth (optionally available), easy moving of the cabinet
- **Ventilation:** integrated air ducts ready for connection (DN 50) to a technical exhaust system



Dimensions	
Width (external)	1102.00 mm
Depth (external)	600.00 mm
Height (external)	800.00 mm
Width (internal)	979.00 mm
Depth (internal)	482.00 mm
Height (internal)	702.00 mm
The available internal dimensions can vary depend	ding on the interior equipment package

Weight / Load	
Weight without interior equipment	233 kg
Distributed load	302.00 kg/m ²
Maximum load	300 kg

Ventilation		
Extraction air	50 DN	
minimum exhaust air quantity 10 times	2 m³/h	
Pressure drop inside the cabinet	1 Pa	

Colouring / Surface finish	
Body colour code	RAL 7035
Body colour	Light grey
Body surface finish	plain
Door / Drawer colour code	RAL 7035
Door / Drawer colour	Light grey
Door / Drawer surface finish	plain

General Information	
Number of drawers	2
Capacity drawer	21.5 litres
Volume of drawer 2	21.5 litres
Customs tariff number	94032080



Available From:

Fire and Safety Centre 15 Atkinsons Way, Foxhills Industrial Estate Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk