



**Schedule 40 Fittings Product**  
**Pool & Spa Fittings**

All Pool & Spa Specialty Fittings have a maximum use service pressure of 150 psi @ 73° F (22° C). Standard pressure de-ratings must be applied for use at elevated temperatures with a maximum service temperature of 140°F (60° C).

Part Number	Size	Std Pk	Mstr Ctn	Prod Code
-------------	------	--------	----------	-----------

**Short Socket Tees**

**Socket Style Sch 40**

Special short-socket end allows close connection at pumps, filters and other areas with minimum available space.

S401-249	2X2X1	25	0	015
S401-251	2x2x1-1/2	25	0	015



**Male Thread Tee (Branch)**

**Socket x Socket x Mipt**

402B-010	1	50	0	040
----------	---	----	---	-----



**Spigot Tee, 2"**

**Spigot x Spigot x Spigot Sch 40**

404A-020	2	30	0	015
----------	---	----	---	-----



**90° Ell, 2"x1-1/2" Reducing, Socket/Spigot**

**2"x2" 90° Street Ell, Socket x Spigot Sch 40**

Handy dual-purpose configuration is 2"x1-1/2" Socket Reducing 90° Ell and also a 2" Socket x 2" Spigot 90° Street Ell.

406-251N	2X1-1/2	10	0	015
----------	---------	----	---	-----



**90° Ell 2-1/2"x2" Reducing Socket/Spigot**

**2-1/2"x2-1/2" 90° Street Ell, Socket x Spigot Sch 40**

Handy dual-purpose configuration is 2-1/2" x 2" Socket Reducing 90° Ell and also a 2-1/2" Socket x 2-1/2" Spigot 90° Street Ell.

406-292N	2-1/2X2 (2-1/2 Spigot)	10	0	040
----------	------------------------	----	---	-----



**90° Spigot Ell, 1-1/2"**

**Spigot x Spigot Sch 40**

422-015	1-1/2	25	0	015
---------	-------	----	---	-----



Part Number	Size	Std Pk	Mstr Ctn	Prod Code
-------------	------	--------	----------	-----------

**45° Street Ell -Short Spigot**

**Spigot x Socket Sch 40**

Special short-spigot end allows close connection in extra-tight spaces.

S427-020	2	10	0	015
----------	---	----	---	-----



**45° Street Ell**

**Spigot x Socket**

427-005	1/2	50	400	040
427-007	3/4	50	0	040
427-010	1	50	0	040
427-012	1-1/4	25	0	040
427-015	1-1/2	25	0	040
427-020	2	25	0	040
427-025	2-1/2	10	0	040
427-030	3	10	0	040
427-040	4	5	0	040
427-050	5	4	0	040
427-060	6	4	0	040
427-080	8	2	0	040
427-100	10	1	0	041
427-120	12	1	0	041
427-140F	14	1	0	047
427-160F	16	1	0	047
427-180F	18	1	0	047
427-200F	20	1	0	047
427-240F	24	1	0	047



**22-1/2° Street Ell**

**Spigot x Socket**

442-005	1/2	50	400	040
442-007	3/4	50	0	040
442-010	1	50	0	040
442-012	1-1/4	20	0	040
442-015	1-1/2	25	0	040
442-020	2	20	0	040
442-025F	2-1/2	1	18	047
442-030	3	5	0	040
442-040	4	4	0	040
442-060	6	4	0	040
442-060F	6	1	5	047
442-080	8	1	4	040
442-080F	8	1	4	047



Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas

JJ DOWNS INDUSTRIAL PLASTICS INC.

416.236.1884
Toronto, ON
JJDOWNS.COM



Schedule 40 Fittings Product  
**Pool & Spa Fittings**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code
<b>22-1/2° Street Ell (continued)</b>				
<b>Spigot x Socket</b>				
442-100F	10	1	0	047
442-120F	12	1	0	047

Part Number	Size	Std Pk	Mstr Ctn	Prod Code
<b>Venturied Tee, Multi Configuration - Socket Style Sch 40</b>				
(continued)				
<b>Individual Nozzles Only</b>				
473-3	3/8" Nozzle	100	600	015

**Grated Coupling, 2" Sch 40**



**Socket Style Sch 40**

Specially designed internal grate at pipe stop gives extra protection to pumps, filters and equipment from damaging gravel and debris.

429GR-020	2	25	0	015
-----------	---	----	---	-----

**120° Wye, 1-1/2"x1"x1"**



**Spigot x Socket x Socket Sch 40**

Unique spigot end take off with 120° branched wye pattern for special distribution connections.

475-21131T	1-1/2X1X1	25	0	015
------------	-----------	----	---	-----

**Smooth Barb Adapter**



**Spigot x Smooth Barb**

Special adapter for making connections to Flexible Vinyl Hose

432-007525	3/4X1/2	100	600	015
432-007775	3/4	50	600	015
432-010775N	1(3/4)X3/4	50	400	015

"N" suffix indicates Nesting - Spigot also serves as serves as size smaller socket

**120° Wye, 2"**



**Socket**

475-020120	2	10	0	015
------------	---	----	---	-----

**Venturied Tee, Multi Configuration - Socket Style Sch 40**



**1-1/2" Socket (2" Spigot) x 1-1/2" Socket x 3/4" Socket (1" Spigot)**

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-210	with 7/16" Nozzle	25	0	015
473-210-1/4	with 1/4" Nozzle	25	0	015
473-210-3/8	with 3/8" Nozzle	25	0	015

**Nesting Union**



**2" Socket x 1-1/2" Socket (2" Spigot) Buna-N O-ring**

235 psi @ 73°F (23°C)

8057-251W	2X1-1/2 (2)	5	0	080
-----------	-------------	---	---	-----

**Nesting Union**



**2" Socket x 1-1/2" Socket (2" Spigot) EPDM O-ring**

235 psi @ 73°F (23°C)

8097-251W	2X1-1/2 (2)	5	0	080
-----------	-------------	---	---	-----

**Venturied Tee, Multi Configuration - Socket Style Sch 40**



**1" Socket x 3/4" Socket (1" Spigot) x 3/4" Socket (1" Spigot)**

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-825	with 7/16" Nozzle	50	0	015
473-825-3/8	with 3/8" Nozzle	50	0	015
473-825-1/4	with 1/4" Nozzle	50	0	015

**Venturied Tee, Multi Configuration - Socket Style Sch 40**



**Individual Nozzles Only**

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-1	7/16" Nozzle	100	600	015
473-2	1/4" Nozzle	100	600	015

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas

JJ DOWNS INDUSTRIAL PLASTICS INC.

416.236.1884
Toronto, ON
JJDOWNS.COM