

CW-325 SINGLE PLY ACRYLIC/ POLYESTER




| Colour | Temperature Range | Stock Sizes | Available Sizes |
|--------|-----------------------------------|-------------|-----------------|
| Black | -29°C to +163°C (-20°F to +325°F) | 2"-8" | 1-1/2"-16" |

| Standard Stock Sizes | Non Standard Lengths |
|----------------------|----------------------|
| 25ft only | Made to order |

Product Information

CW-325- A black single ply acrylic coated polyester fabric hose with both high and low temperature capabilities. Used for air or fume movement. Enclosed spring steel wire reinforcement for crush resistance. Flame retardant to UL 94V-O. For temperatures exceeding 325°F. Use one of the following hi-temp hoses. BDS, GS, FLEX-LOK 1500, FLEX-LOK TFE. CW-325 is an excellent product for overhead vehicle exhaust systems.

Product Applications



Notes

* Pressures based on straight lengths of hose @ 72°F

| Parts Number | I.D. Inches | Approx Weight | Positive Pressure | Negative Pressure | Centreline Bend Radius |
|--------------|-------------|---------------|-------------------|-------------------|------------------------|
| CW-325-2 | 2 | 0.250 | 30 | 29 | 1.60 |
| CW-325-2.5 | 2-1/2 | 0.260 | 30 | 29 | 1.78 |
| CW-325-3 | 3 | 0.280 | 30 | 29 | 2.30 |
| CW-325-4 | 4 | 0.410 | 18 | 29 | 2.80 |
| CW-325-5 | 5 | 0.600 | 14 | 16 | 3.50 |
| CW-325-6 | 6 | 0.690 | 7 | 14 | 3.80 |
| CW-325-7 | 7 | 0.810 | 6 | 8 | 4.50 |
| CW-325-8 | 8 | 0.920 | 5 | 7 | 5.20 |
| CW-325-10 | 10 | 1.100 | 4 | 6 | 6.40 |
| CW-325-12 | 12 | 2.000 | 3 | 5 | 8.00 |



JJ DOWNS INDUSTRIAL PLASTICS INC.



international association of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM