

CW-GP DOUBLE PLY NEOPRENE/ POLYESTER



Colour	Temperature Range	Stock Sizes	Available Sizes
Black	-40°C to +121°C (-40°F to +250°F)	1"-24"	1"-48"

Standard Stock Sizes	Non Standard Lengths
25& 50ft	Multiples of 5ft

Product Information

CW-GP-Double ply neoprene impregnated polyester fabric hose construction, reinforced with a spring steel wire helix. It has excellent crush resistance and tensile strength. The neoprene coating offers excellent abrasion and chemical resistance. Handles positive and negative pressure and is extremely flexible. More durable than double ply cotton hose. CW-GP is UL-94V-0 flame retardant.

Notes

* Pressures based on straight lengths of hose @ 72°F

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
CW-GP-2	2	0.25	30	29.0	2.00
CW-GP-2.5	2-1/2	0.29	30	29.0	1.80
CW-GP-3	3	0.34	30	29.0	2.40
CW-GP-3.5	3-1/2	0.40	30	29.0	2.50
CW-GP-4	4	0.56	30	29.0	3.10
CW-GP-5	5	0.75	17	17.0	3.50
CW-GP-6	6	0.95	11	21.0	4.50
CW-GP-7	7	0.99	8	14.0	5.00
CW-GP-8	8	1.10	6.5	12.0	6.00
CW-GP-9	9	1.20	6	9.0	6.50
CW-GP-10	10	1.30	5	9.0	7.50
CW-GP-12	12	1.50	4.3	4.0	8.00
CW-GP-14	14	2.20	3.6	3.7	10.00
CW-GP-16	16	2.50	3.2	2.5	12.00
CW-GP-18	18	2.80	3	1.8	13.00

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM