



B Series

PART #	DESCRIPTION
SAF050B	3/4" Female Coupler x 1/2" Male NPT
SAF075B	3/4" Female Coupler x 3/4" Male NPT
SAF100B	1" Female Coupler x 1" Male NPT
SAF125B	1" Female Coupler x 1-1/4" Male NPT
SAF150B	1-1/2" Female Coupler x 1-1/2" Male NPT
SAF200B	2" Female Coupler x 2" Male NPT
SAF300B	3" Female Coupler x 3" Male NPT



C Series

PART #	DESCRIPTION
SAF050C	3/4" Female Coupler x 1/2" Hose Barb
SAF075C	3/4" Female Coupler x 3/4" Hose Barb
SAF100C	1" Female Coupler x 1" Hose Barb
SAF125C	1" Female Coupler x 1-1/4" Hose Barb
SAF150C	1-1/2" Female Coupler x 1-1/2" Hose Barb
SAF200C	2" Female Coupler x 2" Hose Barb
SAF300C	3" Female Coupler x 3" Hose Barb



D Series

PART #	DESCRIPTION
SAF050D	3/4" Female Coupler x 1/2" Female NPT
SAF075D	3/4" Female Coupler x 3/4" Female NPT
SAF100D	1" Female Coupler x 1" Female NPT
SAF125D	1" Female Coupler x 1-1/4" Female NPT
SAF150D	1-1/2" Female Coupler x 1-1/2" Female NPT
SAF200D	2" Female Coupler x 2" Female NPT
SAF300D	3" Female Coupler x 3" Female NPT



CAP Series

PART #	DESCRIPTION
SAF075CAP	3/4" CAP for Male Adapter
SAF100125CAP	1" CAP for Male Adapter
SAF150CAP	1-1/2" CAP for Male Adapter
SAF200CAP	2" CAP for Male Adapter
SAF300CAP	3" CAP for Male Adapter

Safety Camlock Coupling features:

- Patented Locking Arms to reduce possibility of unintentional opening of cam levers during use.
- Glass Filled Polypropylene
- 1/2" thru 2" Maximum Operating Pressure 125 psi @ 70°F.
- 3" Maximum Operating Pressure 75 psi @ 70°F.
- E.P.D.M. Gaskets

1/2"series couplings interchange with 3/4" size couplings. Coupling ends are 3/4" size.
 1-1/4"series couplings interchange with 1" size couplings. Coupling ends are 1" size.





A Series

PART #	DESCRIPTION
050A	3/4" Male Adapter x 1/2" Female NPT
075A	3/4" Male Adapter x 3/4" Female NPT
100A	1" Male Adapter x 1" Female NPT
125A	1" Male Adapter x 1-1/4" Female NPT
150125A	1-1/2" Male Adapter x 1-1/4" Female NPT
150A	1-1/2" Male Adapter x 1-1/2" Female NPT
200A	2" Male Adapter x 2" Female NPT
300A	3" Male Adapter x 3" Female NPT
400A	4" Male Adapter x 3" Female NPT



B Series

PART #	DESCRIPTION
050B	3/4" Female Coupler x 1/2" Male NPT
075B	3/4" Female Coupler x 3/4" Male NPT
100B	1" Female Coupler x 1" Male NPT
125B	1" Female Coupler x 1-1/4" Male NPT
150125B	1-1/2" Female Coupler x 1-1/4" Male NPT
150B	1-1/2" Female Coupler x 1-1/2" Male NPT
200B	2" Female Coupler x 2" Male NPT
300B	3" Female Coupler x 3" Male NPT
400B	4" Female Coupler x 4" Male NPT



C Series

PART #	DESCRIPTION
050C	3/4" Female Coupler x 1/2" Hose Barb
075C	3/4" Female Coupler x 3/4" Hose Barb
100C	1" Female Coupler x 1" Hose Barb
125C	1" Female Coupler x 1-1/4" Hose Barb
150125C	1-1/2" Female Coupler x 1-1/4" Hose Barb
150C	1-1/2" Female Coupler x 1-1/2" Hose Barb
200C	2" Female Coupler x 2" Hose Barb
300C	3" Female Coupler x 3" Hose Barb
400C	4" Female Coupler x 4" Hose Barb



D Series

PART #	DESCRIPTION
050D	3/4" Female Coupler x 1/2" Female NPT
075D	3/4" Female Coupler x 3/4" Female NPT
100D	1" Female Coupler x 1" Female NPT
125D	1" Female Coupler x 1-1/4" Female NPT
150125D	1-1/2" Female Coupler x 1-1/4" Female NPT
150D	1-1/2" Female Coupler x 1-1/2" Female NPT
200D	2" Female Coupler x 2" Female NPT
300D	3" Female Coupler x 3" Female NPT
400D	4" Female Coupler x 4" Female NPT

Cam Lever Coupling features:

- Glass Filled Polypropylene
- 1/2" thru 2" Maximum Operating Pressure 125 psi @ 70°F.
- 3" and 4" Maximum Operating Pressure 75 psi @ 70°F.
- E.P.D.M. Gaskets

1/2"series couplings interchange with 3/4" size couplings. Coupling ends are 3/4" size.

1-1/4"series couplings interchange with 1" size couplings. Coupling ends are 1" size.

4" Camlocks have 3 arms

- Product may vary depending on size.



E Series

PART #	DESCRIPTION
050E	3/4" Male Adapter x 1/2" Hose Barb
075E	3/4" Male Adapter x 3/4" Hose Barb
100E	1" Male Adapter x 1" Hose Barb
125E	1" Male Adapter x 1-1/4" Hose Barb
150125E	1-1/2" Male Adapter x 1-1/4" Hose Barb
150E	1-1/2" Male Adapter x 1-1/2" Hose Barb
200E	2" Male Adapter x 2" Hose Barb
300E	3" Male Adapter x 3" Hose Barb
400E	4" Male Adapter x 4" Hose Barb



CAP Series

PART #	DESCRIPTION
075CAP	3/4" CAP for Male Adapter
100125CAP	1" CAP for Male Adapter
150CAP	1-1/2" CAP for Male Adapter
200CAP	2" CAP for Male Adapter
300CAP	3" CAP for Male Adapter
400CAP	4" CAP for Male Adapter

Cam Lever Coupling features:

- Glass Filled Polypropylene
- 1/2" thru 2" Maximum Operating Pressure 125 psi @ 70°F.
- 3" and 4" Maximum Operating Pressure 75 psi @ 70°F.
- E.P.D.M. Gaskets

1/2"series couplings interchange with 3/4" size couplings. Coupling ends are 3/4" size.

1-1/4"series couplings interchange with 1" size couplings. Coupling ends are 1" size.

4" Camlocks have 3 arms

- Product may vary depending on size.



F Series

PART #	DESCRIPTION
050F	3/4" Male Adapter x 1/2" Male NPT
075F	3/4" Male Adapter x 3/4" Male NPT
100F	1" Male Adapter x 1" Male NPT
125F	1" Male Adapter x 1-1/4" Male NPT
150125F	1-1/2" Male Adapter x 1-1/4" Male NPT
150F	1-1/2" Male Adapter x 1-1/2" Male NPT
200F	2" Male Adapter x 2" Male NPT
300F	3" Male Adapter x 3" Male NPT
400F	4" Male Adapter x 4" Male NPT



PL Series

PART #	DESCRIPTION
075PL	3/4" Plug for Female Coupler
100125PL	1" Plug for Female Coupler
150PL	1-1/2" Plug for Female Coupler
200PL	2" Plug for Female Coupler
300PL	3" Plug for Female Coupler
400PL	4" Plug for Female Coupler



Plug with Handle*

*Sold under License,
US Patent Nos. 7,644,734
and 8,397,764

PART #	PRICE ea.	QTY	DESCRIPTION
200PLH	\$18.68	50 / Box	2" Plug with Handle
300PLH	\$28.51	24 / Box	3" Plug with Handle

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM



2" x 3" Series


PART #	DESCRIPTION
300200F	2" Male Adapter x 3" Male NPT
300200A	2" Male Adapter x 3" Female NPT
300B200A	3" Female Coupler x 2" Male Adapter
300200D	3" Female Coupler x 2" Female NPT
SAF300B200A	3" Female Coupler x 2" Male Adapter
SAF300200D	3" Female Coupler x 2" Female NPT

Plug with Handle*



PART #	DESCRIPTION
200PLH	2" Plug with Handle
300PLH	3" Plug with Handle

**Sold under License, US Patent Nos. 7,644,734 and 8,397,764*



Replacement Gasket

PART #	DESCRIPTION
75G	1/2" & 3/4" EPDM Gasket
100G	1" & 1-1/4" EPDM Gasket
150G	1-1/2" EPDM Gasket
200G	2" EPDM Gasket
300G	3" EPDM Gasket
400G	4" EPDM Gasket
75GV	3/4" Viton® Gasket
100GV	1" Viton® Gasket
150GV	1-1/2" Viton® Gasket
200GV	2" Viton® Gasket
300GV	3" Viton® Gasket
75GXT	3/4" Xtra Thick Gasket
100GXT	1" Xtra Thick Gasket
150GXT	1-1/2" Xtra Thick Gasket
200GXT	2" Xtra Thick Gasket
300GXT	3" Xtra Thick Gasket



Garden Hose Couplings

Polypropylene Garden Hose Couplings used to connect a Female GHT to a Male GHT

PART #	SIZE & DESCRIPTION
GLP075AG	3/4" Female GHT x 3/4" Male Adapter
GLP075BG	3/4" Male GHT x 3/4" Female Coupler
GLP075DG	3/4" Female GHT x 3/4" Female Coupler
GLP075FG	3/4" Male GHT x 3/4" Male Adapter

Use either of the valve connectors as a quick shutoff at the end of any garden hose.

Camlock Shims



PART #	DESCRIPTION
SHIM075	3/4" Gasket Shim
SHIM100	1" Gasket Shim
SHIM150	1-1/2" Gasket Shim
SHIM200	2" Gasket Shim
SHIM300	3" Gasket Shim
SHIM400	4" Gasket Shim

NEW TO THE INDUSTRY



- Improves Fluid Flow
- Reduces back pressure on pump seal

PART #		DESCRIPTION
200CSWP90		2" Female Coupler x 2" Hose Barb Sweep



- Improves Fluid Flow
- Reduces back pressure on pump seal

PART #		DESCRIPTION
200FSWP90		2" Male Adapter x 2" Male NPT ; 90°
300FSWP90		3" Male Adapter x 3" Male NPT ; 90°



AL



CL



DL



FL



Spool Adapter



Series

90 Degree Coupling features:

- Glass Filled Polypropylene
- Maximum Operating Pressure 125 P.S.I. @ 70°F
- E.P.D.M. Gaskets

PART #		DESCRIPTION
150A90		1-1/2" Male Adapter x 1-1/2" Female NPT
200A90		2" Male Adapter x 2" Female NPT
150C90		1-1/2" Female Coupler x 1-1/2" Hose Shank
200C90		2" Female Coupler x 2" Hose Shank
150D90		1-1/2" Female Coupler x 1-1/2" Female NPT
200D90		2" Female Coupler x 2" Female NPT
150F90		1-1/2" Male Adapter x 1-1/2" Male NPT
200F90		2" Male Adapter x 2" Male NPT
200FF		2" Male Adapter x 2" Male Adapter
200F45		2" Male Adapter x 2" Male NPT



JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM