

CHALLENGER EPDM GENERAL SERVICE HOSE

CHALLENGER™



Application

An economical EPDM multi purpose hose used in a wide range of air, water, and light agricultural chemical applications. Challenger General Service hose is used in construction, marine, agricultural, and industrial applications.

Construction

Tube- Black EPDM blended rubber
 Reinforcement- Polyester yarn
 Cover- Smooth red abrasion resistant EPDM blend.

Temperature Range

-20°C to +93°C (-4°F to +200°F)

Standard Lengths

25ft multiples + full reel quantities

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Approx. Wt. Per. Ft. Lbs.	Reel Quantities
CHAL-.25-250	1/4	0.51	250	0.110	600 ft = 300 ft + 300 ft
CHAL-.375-250	3/8	0.67	250	0.160	600 ft = 300 ft + 300 ft
CHAL-.5-250	1/2	0.83	250	0.230	600 ft = 300 ft + 300 ft
CHAL-.75-250	3/4	1.14	250	0.400	400 ft = 200 ft + 200 ft
CHAL-1-200	1	1.40	200	0.530	400 ft = 200 ft + 200 ft

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.



JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



member
iapd
international association
of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM