

Challenger Spa Hose

CHALLENGER™



Application

A very flexible hose designed for use in the installation of tubs, spas, swimming pools, filters, and similar water transfer applications.

Construction

Smooth PVC Tube with rigid PVC helix

Temperature Range

-20°C (-4° F) to 65°C (150° F)

Standard Lengths

1-1/2" to 6" - Max Length 100 ft. - Cut to 5 ft. multiples

Notes:

Designed to be glued into Schedule 40 PVC fittings.

Warning: Spa Hose can be susceptible to termite and rodent damage. Do not use underground in areas prone to rodent and insect damage. Warranty does not cover damage caused by outside forces.

Parts No.	O.D. Inches	Max W.P. PSI @ 21°C (70°F)	Vacuum Rating (in Hg) 68F	Approx. Wt. Per. Ft. Lbs.	IPS Size (in.)
SPA-C-.75	1.053	100	28	0.21	3/4
SPA-C-1	1.320	100	28	0.28	1
SPA-C-1.5	1.904	70	28	0.44	1-1/2
SPA-C-2	2.381	70	28	0.58	2

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.



JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



member
iapd
international association
of plastics distribution

416.236.1884

Toronto, ON

JJDOWNS.COM