

Chemical Guidelines

Technical Specifications

This information is provided only as a guide. Actual service life can only be determined by the user, evaluating the elastomer in actual service conditions.

RATINGS CODE:

- A Excellent:** Long service may be expected with little or no effect on elastomer - suitable for continuous service.
- B Good:** Good service may be expected, but elastomer will be affected by the chemical exposure - usually suitable for continuous or intermittent service.
- C Conditional:** Fair service may be expected if chemical exposure is limited or infrequent. Not recommended for continuous, but may give some service if it is the only elastomer present.
- X Not Recommended.** Insufficient Information: No data available at the time of publication to determine an accurate rating, but the elastomer is not expected to perform better than those listed.

COMMON NAME	ASTM DESIGNATION	COMPOSITION
Buna-N or Nitrile	NBR	Nitrile-Butadiene
Cross Linked Polyethylene	XLPE	Cross Linked Polyethylene
EPT or EPDM	EPDM	Ethylene-propylene-diene-terpolymer
Teflon	FEP	Fluorinated Ethylene Propylene
SBR	SBR	Styrene-Butadiene
Hypalon	CSM	Chlorosulfonated polyethylene
Natural	NR	Isoprene (Natural)
Neoprene	CR	Chloroprene
Viton	FKM	Fluorocarbon
Ultra High Molecular Weight Polyethylene	UHMWPE	Polyethylene



JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM