

CLEAR PVC TUBING- FOOD GRADE

Series: **K010**



Application

For handling beverages, food stuffs and liquids where clarity, flexibility and a food grade compound are required. This product complies with FDA, 3A, NSF-51 and NSF-61 requirements.

Construction

Tube- Crystal clear, non-toxic, odourless and taste free PVC compound manufactured in compliance with applicable FDA, 3A, NSF-51 and NSF-61 requirements

Cover- Food grade crystal clear PVC



Temperature Range

-4°C to +35°C (+25°F to +150°F)

Standard Lengths

100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Wall Inches	Approx. Wt. Per. Ft. Lbs.
PVCTUB-.125	1/8	1/4	65	1/16	0.020
PVCTUB-.188-.25	3/16	1/4	50	1/32	0.012
PVCTUB-.188	3/16	5/16	55	1/16	0.027
PVCTUB-.25-.375	1/4	3/8	55	1/16	0.034
PVCTUB-.25-5	1/4	1/2	60	1/8	0.080
PVCTUB-.313	5/16	7/16	50	1/16	0.040
PVCTUB-.375-5	3/8	1/2	45	1/16	0.047
PVCTUB-.375-.625	3/8	5/8	55	1/8	0.107
PVCTUB-.5-.625	1/2	5/8	30	1/8	0.060
PVCTUB-.5-.75	1/2	3/4	45	1/8	0.134
PVCTUB-.625-.75	5/8	3/4	30	1/16	0.082
PVCTUB-.625	5/8	7/8	40	1/8	0.161
PVCTUB-.75	3/4	1	35	1/8	0.188
PVCTUB-.875	7/8	1-1/8	30	1/8	0.214
PVCTUB-1	1	1-1/4	25	1/8	0.241
PVCTUB-1-1.5	1	1-1/2	35	1/4	0.536
PVCTUB-1.25	1-1/4	1-1/2	20	1/8	0.296
PVCTUB-1.5	1-1/2	1-7/8	30	3/16	0.542
PVCTUB-1.5-2	1-1/2	2	35	1/4	0.750
PVCTUB-2	2	2-1/2	35	1/4	0.964

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.



JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



member
iapd
international association
of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM