


CONTRACTORS WATER DISCHARGE LONG LENGTH



Application

For use on construction sites and general water service.

Construction

Tube- Black EPDM
Reinforcement- Multiple spirals of synthetic yarn
Cover- Black smooth EPDM

Standard Lengths

1/4" to 1" - 700' reels
1-1/4" - 550' reels
1-1/2" - 400' reels
All Sizes - 25' multiples

Temperature Range

-40°C to +93°C (-40°F to +200°F)

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Approx. Wt. Per. Ft. Lbs.
CWDT-.25-200	1/4	.50	200	0.080
CWDT-.313-300	5/16	.63	300	0.130
CWDT-.375-200	3/8	.69	200	0.150
CWDT-.375-300	3/8	.72	300	0.170
CWDT-.5-150	1/2	.81	150	0.190
CWDT-.5-300	1/2	.88	300	0.240
CWDT-.625-150	5/8	.94	150	0.230
CWDT-.625-200	5/8	1.00	200	0.290
CWDT-.75-150	3/4	1.13	150	0.330
CWDT-.75-300	3/4	1.16	300	0.400
CWDT-1-150	1	1.43	150	0.410
CWDT-1-200	1	1.43	200	0.490
CWDT-1.25-200	1-1/4	1.78	200	0.790
CWDT-1.5-200	1-1/2	2.03	200	0.900

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.



JJ DOWNS INDUSTRIAL PLASTICS INC.



member
iapd
international association
of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM