

# EPDM RUBBER 60 DUROMETER



## Colour

Black

## Finish

Smooth

## Physical Characteristics

Tensile: 725 PSI

Elongation: 500%

Hardness: 60 SHORE "A" +/- 5

Temperature Range: -30°C to 104°C (-22°F to 220°F)

## Notes

EPDM is a polymer that provides superior properties for outdoor and high ozone environment applications. EPDM rubber also provides better resistance for acids, alkali and ketones than other general rubber sheets. EPDM sheet is commonly used for roofing, automotive and other applications where high temperature (up to 220 F) is required. However, EPDM sheet has poor resistance to fuels, oils and alcohols.

## ISO/ASTM DESIGNATION = EPDM

| Parts No.     | Gauge x Width | Length | Wt. Per SF lbs. |
|---------------|---------------|--------|-----------------|
| EPDMI-.063-48 | 1/16" X 48    | 100 F  | 0.40            |
| EPDMI-.125-48 | 1/8" X 48     | 66 FT  | 0.85            |
| EPDMI-.188-48 | 3/16" X 48    | 66 FT  | 1.22            |
| EPDMI-.25-48  | 1/4" X 48     | 66 FT  | 1.71            |
| EPDMI-.375-48 | 3/8" X 48     | 33 FT  | 2.53            |
| EPDMI-.5-48   | 1/2" X 48     | 50 FT  | 3.38            |

# JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM