

# EVA WEED SPRAY

Series: K4350



## Application

Use for all low pressure agriculture spray applications, including Monsanto LASSO and anhydrous ammonia.

## Construction

Tube- Clear EVA (Ethylene vinyl acetate)  
Reinforcement- Multiple layers of polyester yarn  
Cover- Clear abrasion & weather resistant EVA

## Temperature Range

-23°C to +65°C (-10°F to +150°F)

## Standard Lengths

25ft multiples & 300ft coils

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Approx. Wt. Per. Ft. Lbs.
EVA-.375	3/8	0.59	300	0.070
EVA-.5	1/2	0.72	250	0.090
EVA-.75	3/4	0.97	150	0.130
EVA-1	1	1.31	150	0.240

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.

# JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM