

# FLX-THANE LD POLYURETHANE



Colour	Temperature Range	Stock Sizes	Available Sizes
Black, Clear	-54°C to +107°C (-65°F to +225°F)	2"-12"	2"-18"
Standard Stock Sizes	Non Standard Lengths		
25ft only	Made to order		

## Product Information

FLX-THANE LD - A lighter wall polyurethane hose supported by a narrow pitch spring steel wire helix. Suitable for air and fume ventilation, vapour recovery system and lightweight materials handling, such as sawdust conveying system and gravity flow material handling. Clear is manufactured with FDA acceptable material. Wall Thickness = .015" - 2" .020" - 2-1/2" and above.

## Product Applications



## Notes

\* Pressures based on straight lengths of hose @ 72°F

## Clear

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
FLX-CLD-2	2	0.250	30.0	29.0	2.00
FLX-CLD-2.5	2-1/2	0.350	30.0	19.0	2.75
FLX-CLD-3	3	0.400	30.0	19.0	3.25
FLX-CLD-4	4	0.500	22.0	24.0	3.75
FLX-CLD-5	5	0.600	18.0	13.0	4.50
FLX-CLD-6	6	0.700	15.0	8.0	5.25
FLX-CLD-7	7	0.800	7.0	8.0	5.88
FLX-CLD-8	8	0.900	7.0	2.0	6.50
FLX-CLD-10	10	1.200	6.0	2.0	7.50
FLX-CLD-12	12	1.400	4.0	1.7	9.00
FLX-CLD-14	14	1.600	5.0	1.1	12.00
FLX-CLD-16	16	1.800	4.6	0.7	14.00
FLX-CLD-18	18	2.000	4.1	0.5	16.00



see pg.2

**Black**

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
FLX-BLD-2	2	0.250	30.0	29.0	2.00
FLX-BLD-2.5	2-1/2	0.350	30	19.0	2.75
FLX-BLD-3	3	0.400	30.0	3.25	2.75
FLX-BLD-4	4	0.500	22.0	24.0	3.75
FLX-BLD-5	5	0.600	18.0	13.0	4.50
FLX-BLD-6	6	0.700	15.0	8.0	5.25
FLX-BLD-7	7	0.800	7.0	8.0	5.88
FLX-BLD-8	8	0.900	7.0	2.0	6.50
FLX-BLD-10	10	1.200	6.0	2.0	7.50
FLX-BLD-12	12	1.400	4.0	1.7	9.00
FLX-BLD-14	14	1.600	5.0	1.1	12.00
FLX-BLD-16	16	1.800	4.6	0.7	14.00
FLX-BLD-18	18	2.000	4.1	0.5	16.00



JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM