

FLX-THANE SD STATIC DISSIPATIVE POLYURETHANE



Colour	Temperature Range	Stock Sizes	Available Sizes
Black, Clear	-54°C to +107°C (-65°F to +225°F)	None	2"-12"
Standard Stock Sizes	Non Standard Lengths		
None	Made to order		

Product Information

FLX-THANE SD- A durable urethane hose has excellent resistance to abrasion, cutting and gouging. Medium weight ether-type, static dissipative polyurethane wall. Supported by bronze coated spring steel wire helix for crush resistance and efficient flow characteristics. Suitable for chemical fume exhausting, lightweight material handling, and dust collection applications where static electricity is present. Clear is manufactured with FDA acceptable materials. Wall thickness= .030".

Product Applications



Notes

* Pressures based on straight lengths of hose @ 72°F

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
FLX-BSD-2	2	0.250	30	29	2.00
FLX-BSD-3	3	0.400	29	29	3.00
FLX-BSD-4	4	0.700	25	29	4.00
FLX-BSD-6	6	1.000	19	15	6.00
FLX-BSD-8	8	1.500	14	9	8.00
FLX-BSD-10	10	1.600	11	4	8.00
FLX-BSD-12	12	2.000	10	2.2	10.00
FLX-CSD-2	2	0.250	30	29	2.00
FLX-CSD-3	3	0.400	29	29	3.00
FLX-CSD-4	4	0.700	25	29	4.00
FLX-CSD-6	6	1.000	19	15	6.00
FLX-CSD-8	8	1.500	14	9	8.00
FLX-CSD-10	10	1.600	11	4	8.00
FLX-CSD-12	12	2.000	10	2.2	10.00




JJ DOWNS INDUSTRIAL PLASTICS INC.

416.236.1884
Toronto, ON
JJDOWNS.COM