

FLX-Thane SE



Colour	Temperature Range	Stock Sizes	Available Sizes
Clear	-54°C to +107°C (-65°F to +225°F)	2"-24"	2"-24"

Standard Stock Sizes	Non Standard Lengths
25 ft, 50 ft (14" & above in 25 ft only)	Made to order

Product Information

Self-extinguishing medium weight clear polyurethane hose reinforced with a bronze coated spring steel wire helix. Halogen-free. Good compressibility. Great abrasion resistance & high tear strength. Superior chemical resistance. Excellent flexibility. Designed for applications with wide temperature ranges. Good low temperature flexibility. Manufactured with flame retardant materials. Wall Thickness = .030" Standard Max. Inside Diameter = 12"

Product Applications



Notes

* Pressures based on straight lengths of hose @ 72°F

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
FLX-SE-2	2	0.250	30	29	2
FLX-SE-2.5	2-1/2	0.320	30	29	2.5
FLX-SE-3	3	0.400	29	29	3
FLX-SE-4	4	0.700	25	29	4
FLX-SE-5	5	0.900	22	17	5
FLX-SE-6	6	1.000	19	15	6
FLX-SE-8	8	1.500	14	9	8
FLX-SE-10	10	1.600	11	4	8
FLX-SE-12	12	2.000	10	2.2	10



JJ DOWNS INDUSTRIAL PLASTICS INC.



member
iapd
international association
of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM