

FLX-THANE VHD POLYURETHANE



Colour	Temperature Range	Stock Sizes	Available Sizes
Clear Black	-54°C to +107°C (+65°F to +225°F)	None	4"-24"
Standard Stock Sizes	Non Standard Lengths		
25ft only	Made to order		

Product Information

FLX-THANE VHD- A very heavy weight polyurethane hose reinforced with a spring steel coated wire helix (sizes 14" and above not available with a coated wire) Great abrasion resistance and high tear strength. Ideal for severe service applications where flexibility is required. Clear is manufactured with FDA acceptable materials. Wall thickness= .060

Product Applications



Notes

* Pressures based on straight lengths of hose @ 72°F

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
FLX-VHD-4	4	1.000	34	29	4.00
FLX-VHD-5	5	1.300	33	17	5.00
FLX-VHD-6	6	1.500	32	15	6.00
FLX-VHD-7	7	1.800	31	12	7.00
FLX-VHD-8	8	1.900	29	9	8.00
FLX-VHD-10	10	2.200	25	4	10.00
FLX-VHD-12	12	2.600	20	2.5	12.00
FLX-VHD-14	14	3.800	18	3.5	14.00
FLX-VHD-16	16	4.200	15	2.5	16.00
FLX-VHD-18	18	4.800	12	1.5	18.00

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM