

FSP-2 DOUBLE PLY PVC/ POLYESTER



Colour	Temperature Range	Stock Sizes	Available Sizes
Black	-29°C to +82°C (-20°F to +180°F)	3"-12"	3"-12"

Standard Stock Sizes	Non Standard Lengths
25ft only	Made to order

Product Information

FSP-2-A double ply flame retardant PVC coated polyester fabric construction with an enclosed spring steel wire helix & external PVC wearstrip. FSP-2 offers superior chemical resistance, low friction loss and is flame retardant to UL 94V-O.

Product Applications



Notes

* Pressures based on straight lengths of hose @ 72°F

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
FSP-2-3	3	0.500	13	29	2.80
FSP-2-4	4	0.720	10	24	3.70
FSP-2-5	5	0.890	8	13	4.70
FSP-2-6	6	1.060	7	7.3	5.30
FSP-2-7	7	1.240	6	5	6.50
FSP-2-8	8	1.480	4	7	6.90
FSP-2-10	10	1.840	3	3.7	8.60
FSP-2-12	12	2.200	2.6	2.2	10.00

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM