


FT SERIES PVC FOOD SUCTION & DISCHARGE

Smooth Cover Clear Helix



Application



Can be used for any liquids or dry materials for human consumption. Suitable for full vacuum. Complies with all applicable FDA and 3A requirements.

Construction

Tube- Crystal clear PVC compounded from non-toxic ingredients in compliance with applicable FDA requirements.

Reinforcement- Clear PVC Helix for suction applications

Cover- Food grade crystal clear PVC with smooth cover (SF) or corrugated cover (CF)

Temperature Range

-20°C to +70°C (-4°F to +158°F)

Standard Lengths

100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Bend Radius	Approx. Wt. Per. Ft. Lbs.
SF-.75	3/4	0.94	86	3	0.160
SF-1	1	1.28	86	3	0.260
SF-1.25	1-1/4	1.56	79	4	0.370
SF-1.5	1-1/2	1.80	72	6	0.440
SF-2	2	2.36	72	8	0.740
SF-2.5	2-1/2	2.88	72	10	1.010
SF-3	3	3.42	62	11	1.210
SF-4	4	4.51	55	18	2.010
SF-5	5	5.51	40	28	2.410
SF-6	6	6.59	30	48	3.280

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.



JJ DOWNS INDUSTRIAL PLASTICS INC.



member
iapd
international association
of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM