

Flex-Tube PV



Temperature Range

-7°C to +71°C (20°F to +160°F)

Stock Sizes

1.5"-12"

Available Sizes

1.5"-12"

Standard Stock Sizes

12ft, 25ft

Non Standard Lengths

None

Product Information

Medium weight clear co-extruded PVC hose with a rigid black external PVC helix. Ultra smooth interior wall assures efficient airflow. Very flexible & crush resistant. Spiral co-extruded engineered construction. Helix acts as a wearstrip. Wall Thickness = .026" (1.5"), .030" (2" to 3"), .032" (4"), .035" (5" to 8"), .040" (9" to 12"). OEM lengths & colors available. Available in a flame retardant version (Flex-Tube PV-FR). Cuffs available.

Product Applications



Notes

* Pressures based on straight lengths of hose @ 72°F

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
FLEX-TUBE-PV-4	4	0.720	16	14	4
FLEX-TUBE-PV-5	5	0.920	17	12	5.25
FLEX-TUBE-PV-6	6	1.110	12	10	6.25
FLEX-TUBE-PV-7	7	1.320	11	10	7
FLEX-TUBE-PV-8	8	1.500	10	6	8

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM