



Valves Product
Globe Valves



Pressure Rating @ 73°F (23°C), Water
150 psi

Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

**All Valves Assembled with Silicone-Free,
Water Soluble Lubricant
Suitable for Vacuum Service**

CPVC Internal Repair Kits

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	GL-ERK-025C	GL-VRK-025C	1	0	299
3	GL-ERK-030C	GL-VRK-030C	1	0	299
4	GL-ERK-040C	GL-VRK-040C	1	0	299
6	GL-ERK-060C	GL-VRK-060C	1	0	299

Internal Repair Kit includes 1-Bonnet O-ring along with a factory assembled (required) internal component replacement unit consisting of Bonnet assembled with Stem/O-rings, Seat & Seal Carrier components. Install in valve using existing valve Bolts/Nuts/Washers, and Handle/Nut.

PVC Flanged Ends

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	6013-025	6023-025	6033-025	1	0	620
3	6013-030	6023-030	6033-030	1	0	620
4	6013-040	6023-040	6033-040	1	0	620
6	6013-060	6023-060	6033-060	1	0	620

CPVC Flanged Ends

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	6023-025C	6033-025C	1	0	622
3	6023-030C	6033-030C	1	0	622
4	6023-040C	6033-040C	1	0	622
6	6023-060C	6033-060C	1	0	622

PVC Internal Repair Kit

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	GL-BRK-025	GL-ERK-025	GL-VRK-025	1	0	299
3	GL-BRK-030	GL-ERK-030	GL-VRK-030	1	0	299
4	GL-BRK-040	GL-ERK-040	GL-VRK-040	1	0	299
6	GL-BRK-060	GL-ERK-060	GL-VRK-060	1	0	299

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas

JJ DOWNS INDUSTRIAL PLASTICS INC.

416.236.1884 Toronto, ON JJDOWNNS.COM