

Kanaline Blue Water Suction



Application

Heavy-duty suction and discharge hose with increased flexibility for use in colder environment applications, where more flexibility is desired.

Construction

Tube- Smooth blue synthetic braiding
 Reinforcement- Rigid PVC helix
 Cover- Flexible cold weather PVC

Temperature Range

-40°C to +60°C (-40°F to +140°F)

Standard Lengths

100ft

| Parts No. | I.D. Inches | O.D. Inches | Max W.P. @ 70°F/20°C | Bend Radius | Vacuum Rating (in Hg) 68F | Approx. Wt. Per. Ft. Lbs. | Standard Lengths |
|----------------|-------------|-------------|-------------------------|----------------|------------------------------------|---------------------------------|---------------------|
| K-LINEBLUE-1.5 | 1-1/2 | 2.10 | 75 | 2.0 | 28.0 | 0.47 | 60, 100 |
| K-LINEBLUE-2 | 2 | 2.60 | 70 | 3.0 | 28.0 | 0.70 | 60, 100 |
| K-LINEBLUE-3 | 3 | 3.70 | 70 | 5.0 | 28.0 | 1.13 | 60, 100 |
| K-LINEBLUE-4 | 4 | 4.80 | 60 | 7.0 | 28.0 | 1.74 | 60, 100 |
| K-LINEBLUE-6 | 6 | 7.30 | 50 | 9.0 | 28.0 | 3.88 | 60, 100 |
| K-LINEBLUE-8 | 8 | 9.50 | 40 | 15.0 | 28.0 | 5.54 | 15, 20, 25 |
| K-LINEBLUE-10 | 10 | 11.63 | 30 | 24.5 | 28.0 | 8.68 | 20, 25, 40 |

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM