EKING LAWIESHIELD

Upgrade to King FlameShield ASTM E-84 Class A Flame Compliance and CAN/ULC-S102 for Canadian Compliance

King Plastic Corporation HDPE products with King FlameShield are improved in physical properties and cost effective compared to competing materials. We offer a Class A upgrade that improves the material's overall physical properties to be more resistant to burning under flammable conditions.

ASTM E-84 is the primary standard used worldwide for contractors, architects and engineers to improve product quality and enhance safety. Additional details are available at astm.org

Applications

- Bathroom Partitions
- Case Goods
- Contract Furniture
- Decorative Ceiling Panels
- Interior Signage
- Lockers
- Shelving
- Wall Panels



Specifications

Please refer to specific product

Properties	Units	ASTM	Nominal Values	
Density	g/cc	D1505	1.04	
Tensile Strength @ Break	psi	D638	1,170	
Tensile Strength @ Yield	psi	D638	3,780	
Tensile Modulus of Elasticity	psi	D638	183,000	
Elongation @ Break	%	D683	53	
Elongation @ Yield	%	D638	8.6	
Flexural Modulus	psi	D790	179,000	
Flexural Stress @ 5% Strain	psi	D790	4,330	
Durometer	Shore D	D2240	71	
Vicat Softening Temp.	°C (°F)	D1525	129°C (264°F)	
Heat Deflection Temp. 66 psi	°C (°F)	D648	86.6°C (188°F)	
Thermal Expansion	in./in./°F	D696	6 x 10 ⁻⁵	

Properties	Units	ASTM	Class A	
Surface Burning Characteristics	FSI & SDI	E84	20 & 60	
Surface Burning Characteristics	FSV & SDV	ULC-S102	20 & 65	

All values are determined on specimens prepared according to ASTM standards. Nominal values should not be interpreted as specifications. For ASTM E-84 Class B, please call customer service.

Tolerance information:

Please refer to specific product information

Disclaimer: FlameShield will affect finish and color

