



Colour

**Temperature Range** 

**Stock Sizes** 

AvailableSizes

Black

-51°C to +135°C (-60°F to +275°F)

1.5"-16"

1.5"-16"

**Standard Stock Sizes** 

**Non Standard Lengths** 

25', 50' (14" & above in 25' only)

Made to order

## **Product Information**

Light weight black thermoplastic rubber hose reinforced with a spring steel wire helix. Excellent compressibility & flexibility. Designed for applications with wide temperature ranges. Great moisture & UV resistance. Excellent chemical resistance. Smooth interior assures minimal friction loss & efficient air flow. Wall Thickness = .020". Available with factory-installed 2" soft cuffs. Standard Max. Inside Diameter = 12", consult sales team for pricing & minimums on larger sizes.

## **Product Applications**

AIR

**FUME** 

DUST

MATERIAL

## **Notes**

\* Pressures based on straight lengths of hose @ 72°F

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
P-LT-2	2	0.180	12	29	2
P-LT-2.5	2-1/2	0.210	12	29	2.46
P-LT-3	3	0.240	7.7	11	2.92
P-LT-4	4	0.310	5.1	9	3.58
P-LT-5	5	0.390	4.1	4.7	3.79
P-LT-6	6	0.460	3.4	2.7	4
P-LT-7	7	0.480	2.4	2.8	4.25
P-LT-8	8	0.560	2.1	1.9	4.5
P-LT-10	10	0.690	1.7	1	5.8
P-LT-12	12	0.840	1.4	0.6	7
P-LT-14	14	0.970	1.2	0.4	8.1
P-LT-16	16	1.100	1.07	0.24	9.3





416.236.1884

Toronto, ON

JJDOWNS.COM