# Mark 2



#### **Temperature Range**

-40°C to +60°C (-40°F to +140°F)

#### **Stock Sizes**

1.5"-4"

#### **AvailableSizes**

1.5"-4"

## **Standard Stock Sizes**

25ft, 50ft

### **Non Standard Lengths**

None

#### **Product Information**

Medium weight clear polyethylene hose reinforced with a translucent integral polyethylene helix. Ideal for insulation blowing applications. Easy to handle. Translucent walls offer easy monitoring of material flow and blockage. Convoluted interior design creates efficient air flow that aerates insulation materials & increases machine efficiency with regard to coverage & density. Crush resistant. Manufactured with FDA acceptable materials. Available with different color helixes to match OEM equipment.

# **Product Applications**

AIR	FUME	DUST	MATERIAL
-----	------	------	----------

# **Notes**

\* Pressures based on straight lengths of hose @ 72°F

Parts Number	I.D. Inches	Approx Weight	Positive Pressure	Negative Pressure	Centreline Bend Radius
P-MK2-1.5	1-1/2	0.180	16	29	2.2
P-MK2-2	2	0.230	14	29	3.5
P-MK2-2.5	2-1/2	0.350	13.5	14	4
P-MK2-3	3	0.420	12	9	5
P-MK2-3.5	3-1/2	0.450	11	6	6
P-MK2-4	4	0.550	10	4	6.25

