



Valves Product
Needle Valves



PP Needle Valve

Size	Threaded	SR Threaded	Std Pk	Mstr Pk	Prod Code
------	----------	-------------	--------	---------	-----------

Globe Pattern

1/4	5591-002P		1	18	219
3/8	5591-003P		1	18	219
1/2		5591-005PSR	1	18	219

Angle Pattern

1/4	5691-002P		1	18	219
3/8	5691-003P		1	18	219
1/2		5691-005PSR	1	18	219

Pressure Rating @ 73°F (23°C), Water
 PVC or CPVC 235 psi
 PP 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 PP = 180°F (82°C)

Solid PTFE Stem Seals
 No Elastomer or Lubricants used
 Valves include Panel Mounting Nut

PVC Needle Valve

Size	Threaded	Socket	SR Threaded	Std Pk	Mstr Pk	Prod Code
------	----------	--------	-------------	--------	---------	-----------

Globe Pattern

1/4	5591-002	5592-002		1	18	218
3/8	5591-003	5592-003	5591-003SR	1	18	218
1/2	5591-005	5592-005	5591-005SR	1	18	218

Angle Pattern

1/4	5691-002	5692-002		1	18	218
3/8	5691-003	5692-003		1	18	218
1/2	5691-005	5692-005	5691-005SR	1	18	218

CPVC Needle Valve

Size	Threaded	Socket	SR Threaded	Std Pk	Mstr Pk	Prod Code
------	----------	--------	-------------	--------	---------	-----------

Globe Pattern

1/4	5591-002C	5592-002C		1	18	219
3/8	5591-003C	5592-003C	5591-003CSR	1	18	219
1/2	5591-005C	5592-005C	5591-005CSR	1	18	219

Angle Pattern

1/4	5691-002C	5692-002C		1	18	219
3/8	5691-003C	5692-003C		1	18	219
1/2	5691-005C	5692-005C	5691-005CSR	1	18	219

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas

JJ DOWNS INDUSTRIAL PLASTICS INC.

416.236.1884

Toronto, ON

international association
of plastics distribution

JJDOWNS.COM