

# PVC GENERAL PURPOSE

Series: K1154



## Application

A moderately priced general purpose PVC hose for handling air, water, oil, chemicals, insecticides and fungicides. Good abrasion resistance.

## Construction

Tube- Smooth black PVC blend  
Reinforcement- Two layers of synthetic yarn  
Cover- Smooth red weather & abrasion resistant PVC blend

## Temperature Range

-5°C to +65°C (-25°F to +150°F)

## Standard Lengths

25ft multiples & 500ft reels

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Approx. Wt. Per. Ft. Lbs.
PVCGP-.25-250	1/4	0.50	250	0.080
PVCGP-.735-250	3/8	0.63	250	0.110
PVCGP-.5-250	1/2	0.75	250	0.140
PVCGP-.75-175	3/4	1.03	175	0.220
PVCGP-1-150	1	1.31	150	0.310

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.

# JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM