


PVC MARINE SANITARY

Series: **MH**

tigerflex[®]



Application

flexible for use in confined bilge areas.

Construction

Tube-Smooth cream coloured PVC
Reinforcement- PVC helix
Cover-Corrugated cream coloured PVC

Temperature Range

-20°C to +65°C (-4°F to +150°F)

Standard Lengths

50ft/ 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Bend Radius	Approx. Wt. Per. Ft. Lbs.
PVCMS-1	1	1.22	45	1	0.150
PVCMS-1.25	1-1/4	1.49	40	1.5	0.200
PVCMS-1.5	1-1/2	1.77	40	2	0.250
PVCMS-2	2	2.32	35	2.5	0.310

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM