


POLYWIRE VACUUM/ TRANSFER



Application

Where full vacuum and a clear non-collapsible hose is required. Can be used for milk, beverages and pharmaceuticals. This product complies with all applicable FDA, 3A, NSF-51 and NSF-61 requirements.

Construction

Tube- Crystal clear PVC compounded from non-toxic ingredients in compliance with applicable FDA, 3A, NSF-51, NSF-61 requirements
 Reinforcement- Spring steel wire helix
 Cover- Crystal clear PVC compounded from non-toxic ingredients in compliance with app

Temperature Range

-4°C to +65°C (+25°F to +150°F)

Standard Lengths

50ft/100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Approx. Wt. Per. Ft. Lbs.
CV-.25	1/4	0.50	250	0.100
CV-.375	3/8	0.63	150	0.130
CV-.5	1/2	0.81	150	0.210
CV-.625	5/8	1.00	150	0.300
CV-.75	3/4	1.13	150	0.360
CV-1	1	1.38	100	0.440
CV-1.25	1-1/4	1.75	100	0.370
CV-1.5	1-1/2	2.00	100	0.420
CV-2	2	2.50	100	0.560

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.



JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



member
iapd
international association
of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM