

# PREMIUM POLYURETHANE SELF-RETRACTING AIR

COUPLED w/ MALE SWIVELS



**Construction**

Blue polyurethane, highly abrasion resistant and non-marking. Superior oil resistance, complies with RMA class A designation. Each length has 4" & 20" pigtails.

**Temperature Range**

-18°C to +85°C (0°F to +150°F)

**Notes**

Self-retracting air hose fittings cannot be used on this hose. We recommend machined brass fittings attached with pinch clamps or ferrules. Working length is 80% of the normal length described \*Other lengths available upon request\*

Parts No.	I.D. Inches	Length Extended ft.
PU14X10	1/4	10
PU14X15	1/4	15
PU14X20	1/4	20
PU14X25	1/4	25
PU14X50	1/4	50
PU15X15	3/8	15
PU15X20	3/8	20
PU15X25	3/8	25
PU15X50	3/8	50

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.



**JJD**

JJ DOWNS INDUSTRIAL PLASTICS INC.



member  
**iapd**  
international association  
of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM