RIBBED RUBBER MATTING



Physical Characteristics

Tensile: 435 PSI Elongation: 300%

Hardness: 70 SHORE "A" +/- 5

Temperature Range: -20°C to 80°C (-4°F to 176°F)

Notes

A low cost industrial commercial safety floor mat or runner available in customized widths to suit your toughest applications. The unique compound of polymer rich rubber provides outstanding wear resistance and durability.

ISO/ASTM DESIGNATION= SBR

Parts No.	Gauge x Width	Length	Wt Per LY	Colour	Ribbed
RMBW125-24	1/8	25YDS	4.50	Black	Wide
RMBW125-36	1/8	25YDS	7.00	Black	Wide
RMBW125-36-50	1/8	50YDS	7.00	Black	Wide
RMBW125-48	1/8	25YDS	9.00	Black	Wide
RMGW125-36	1/8	25YDS	7.00	Grey	Wide
RMBRW125-36	1/8	25YDS	7.00	Brown	Wide
RMBW25-36	1/4	25YDS	14.00	Black	Wide
RMBW25-48	1/4	25YDS	18.50	Black	Wide
RMBF125-36	1/8	25YDS	7.00	Black	Fine
RMBF125-48	1/8	25YDS	9.00	Black	Fine





ON JJDOWNS.COM