

RUBBER PUSH-ON

Series: FLEX LOC



Application

Oil resistant hose for use with push-on fittings.

Construction

Tube- Black nitrile, RMA Class A

Reinforcement- High tensile synthetic yarn

Cover- Black, blue, grey, green, yellow, or red Nitrile / PVC RMA Class A

Temperature Range

-29°C to +82°C (-20°F to +180°F)

Standard Lengths

25ft multiples, 250ft or 700ft reels

Notes

Examples of Part Number- 3/8" COLOUR part # = PUSRCOLOUR-.375 1/2" Green= PUSRGREEN-.5 (5/8" and 3/4" available in black only)

Colour

Yellow, blue, grey, red, black or green

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Approx. Wt. Per. Ft. Lbs.
PUSRCOLOUR-.25	1/4	0.50	250	0.100
PUSRCOLOUR-.375	3/8	0.625	250	0.130
PUSRCOLOUR-.5	1/2	0.75	250	0.160
PUSRBLK-.625	5/8	0.90	250	0.220
PUSRBLK-.75	3/4	1.03	250	0.250

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM