


SERIES K3150 CLEAR REINFORCED PVC FOOD GRADE

Series: K3150



Application



Air, drinking water, mild chemicals and alkalis. This product complies with all applicable FDA, 3A, NSF-51 and NSF-61 requirements.

Construction

Tube- Clear smooth PVC. NSF-51 & NSF-61 certified material
 Reinforcement- High tensile synthetic braid
 Cover- Clear, smooth PVC. NSF-51 & NSF-61 certified material

Temperature Range

-4°C to +65°C (+25°F to +150°F)

Standard Lengths

100ft / 300ft coils up to 1/2"
 200ft coils 5/8" to 1"
 100ft coils 1-1/4 to 2"

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Approx. Wt. Per. Ft. Lbs.
CRF-.188	3/16	.375	250	0.040
CRF-.25	1/4	.438	250	0.060
CRF-.313	5/16	.531	250	0.080
CRF-.375	3/8	.594	225	0.090
CRF-.5	1/2	.750	200	0.130
CRF-.625	5/8	.891	200	0.180
CRF-.75	3/4	1.031	150	0.220
CRF-1	1	1.300	125	0.300
CRF-1.25	1-1/4	1.620	100	0.450
CRF-1.5	1-1/2	1.938	100	0.640
CRF-2	2	2.490	75	0.940

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.



JJ DOWNS INDUSTRIAL PLASTICS INC.



member
iapd
international association
of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM