

# SPA HOSE

Series: **FMCR**



**tigerflex**®



## Application

A very flexible hose designed for use in the installation of tubs, spas, swimming pools, filters, and similar water transfer applications.

## Construction

Tube- Smooth PVC  
Reinforcement- PVC helix  
Cover- Solid cream PVC

## Temperature Range

-20°C to +65°C (-4°F to +150°F)

## Standard Lengths

100ft no cutting

Parts No.	O.D. Inches	Max W.P. PSI @ 21°C (70°F)	Vacuum Rating (in Hg) 68F	Approx. Wt. Per. Ft. Lbs.	IPS Size (in.)
SPA-.5	0.850	100	28.0	0.140	1/2
SPA-.75	1.053	100	28.0	0.210	3/4
SPA-1	1.320	100	28.0	0.280	1
SPA-1.25	1.663	80	28.0	0.370	1-1/4
SPA-1.5	1.904	70	28.0	0.440	1-1/2
SPA-2	2.381	70	28.0	0.580	2

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.



JJ DOWNS INDUSTRIAL PLASTICS INC.



member  
iapd  
international association  
of plastics distribution

416.236.1884
Toronto, ON
JJDOWNS.COM