

STAINLESS STEEL T-BOLT CLAMPS- 304 S.S.



Product Information

Stainless Steel T-Bolt clamps are used where there is risk of corrosion such as marine, coolant and food applications. These clamps are used where gear clamps do not provide adequate strength. They have a large size range and are tightened with a standard socket wrench. The band has a beveled edge which helps to prevent damage to the hose cover when tightened. The band, screw, and housing are all SS304.

Notes

Please Note: Check the hose O.D. before ordering

Parts No.	Size Range Inches Min.	Size Range Inches Max.	Approx Weight	Torque Ft Lbs	Band Width
TBOLTS-17-19	22/32	24/32	0.090	4	3/4
TBOLTS-20-22	25/32	28/32	0.090	4	3/4
TBOLTS-23-25	29/32	1	0.092	4	3/4
TBOLTS-26-28	1-1/32	1-3/32	0.094	4	3/4
TBOLTS-29-31	1-5/32	1-7/32	0.117	7	3/4
TBOLTS-32-35	1-9/32	1-12/32	0.119	7	3/4
TBOLTS-36-39	1-13/32	1-17/32	0.123	7	3/4
TBOLTS-40-43	1-18/32	1-22/32	0.130	7	3/4
TBOLTS-44-47	1-23/32	1-27/32	0.163	7	3/4
TBOLTS-48-51	1-28/32	2	0.165	7	3/4
TBOLTS-52-55	2-2/32	2-5/32	0.172	7	3/4
TBOLTS-56-59	2-7/32	2-10/32	0.174	7	3/4
TBOLTS-60-63	2-11/32	2-15/32	0.175	7	3/4
TBOLTS-64-67	2-17/32	2-20/32	0.187	15	3/4
TBOLTS-68-73	2-22/32	2-28/32	0.254	15	1
TBOLTS-74-79	2-29/32	3-3/32	0.264	15	1
TBOLTS-80-85	3-5/32	3-10/32	0.271	15	1
TBOLTS-86-91	3-12/32	3-18/32	0.275	15	1
TBOLTS-92-97	3-20/32	3-26/32	0.290	15	1
TBOLTS-98-103	3-27/32	4-2/32	0.303	15	1
TBOLTS-104-112	4-3/32	4-12/32	0.313	15	1



see pg.2

STAINLESS STEEL T-BOLT CLAMPS- 304 S.S.

TBOLTS-113-121	4-14/32	4-24/32	0.318	15	1
TBOLTS-122-130	4-25/32	5-4/32	0.330	26	1
TBOLTS-131-139	5-5/32	5-15/32	0.396	26	1
TBOLTS-140-148	5-16/32	5-26/32	0.488	26	1
TBOLTS-149-161	5-28/32	6-11/32	0.499	26	1
TBOLTS-162-174	6-12/32	6-27/32	0.506	26	1
TBOLTS-227-239	8-30/32	9-13/32	0.607	26	1

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.

416.236.1884

JJDOWNS.COM

Toronto, ON

