

YELLOW CONTRA-AIR RUBBER AIR HOSE



Application

A highly portable, lightweight, high pressure air hose. Contra-Air's nitrile construction makes this product ideal where oil is a factor. (only suitable for handling petroleum products with an aromatic content under 30%.) Contra-Air's lightweight construction makes this hose ideal to be used as a 1" driller's water supply hose.

Construction

Tube- Yellow abrasion and oil resistant nitrile
Reinforcement- Circular woven 100% polyester yarn
Cover- Yellow nitrile, resistant to abrasion, oil and weathering
Branding- Unbranded

Temperature Range

-30°C to +100°C (-22°F to +212°F)

Standard Lengths

3/4" - 25ft multiples & 100ft coils
1" to 4" - 25ft multiples & 300ft coils

Parts No.	I.D. Inches	O.D. Inches	Max W.P. @ 70°F/20°C	Approx. Wt. Per. Ft. Lbs.
CONAIR-.75	3/4	0.98	300	0.200
CONAIR-1	1	1.24	300	0.173
CONAIR-1.5	1-1/2	1.783	300	0.248
CONAIR-2	2	2.29	300	0.340
CONAIR-2.5	2-1/2	2.85	300	0.400
CONAIR-3	3	3.40	250	0.521

Working pressures are calculated at 70 degrees F (20 degrees C). Maximum working pressure decreases as temperature increases. Pressure ratings can only be achieved using proper coupling procedures. Bend radius is calculated at 70 degrees F (20 degrees C). Flexibility may vary at different temperatures. Please contact JJD if you have concerns regarding your application.

JJD

JJ DOWNS INDUSTRIAL PLASTICS INC.



416.236.1884

Toronto, ON

JJDOWNS.COM