

## Drain Valves


**Model 793** Part No. 401500, 150 psig (10.3 bar)  
Part No. 401503, 250 psig (17.3 bar)

### Drain Valve

- Automatically removes water from compressed air tanks, air separators and after-coolers
- Minimum air loss
- ½" NPT outlet, ½" NPT side inlet, ¾" NPT top inlet
- Cast iron body and cover, stainless steel interior
- Maximum pressure 250 psig (17.3 bar)
- Maximum hydrostatic pressure 350 psig (24.2 bar)



**Drain Valve  
Model 793**



### CAPACITY:

#### Discharge Orifice

- for operating pressures up to 150 psig (10.3 bar), ¾<sup>32</sup>" (2.4mm) seat
- for operating pressures over 150 psig (10.3 bar), ¾<sup>64</sup>" (2mm) seat

Model 793 Capacity		
Pressure psig (bar)	lbs. of water/hr. (kg of water/hr)	
	¾ <sup>32</sup> " (2.4mm) Orifice	¾ <sup>64</sup> " (2mm) Orifice
250 (17.3)	—	900 (408)
200 (13.8)	—	800 (360)
150 (10.3)	1200 (545)	690 (315)
125 (8.6)	1100 (500)	630 (285)
100 (6.9)	975 (442)	570 (258)
80 (5.5)	870 (394)	510 (231)
50 (3.5)	690 (312)	400 (181)
30 (2.1)	530 (240)	315 (143)
15 (1.0)	375 (170)	220 (100)